

# Prof. James R. Wait and Mining Production Technology—An Appreciation

A. C. Tripp, R. McNearny, and C. Furse

**Abstract**—Prof. James R. Wait examined electromagnetic (EM) wave propagation in many situations of interest to mining production, including propagation in tunnels, propagation along extended conductors such as cables and drill stems, and propagation in coal seams. This work remains relevant, both to the mining engineer interested in the EM environment of an operating mine and to the electrical engineer interested in verifying new computational techniques and in extending the scope of EM technology in mining production. Late work in EM focussing in a geological environment is relevant to “next generation” geophysical monitoring equipment.

**Index Terms**—Geologic measurements, mining industry.

## I. INTRODUCTION

JAMES Wait began his career considering electromagnetic (EM) applications to mining and his contributions to the field were profound. His publications on induced polarization and the EM response of layered earths have been cited constantly by workers in exploration and resource evaluation. His work in transient exploration was innovative and predated mainstream adoption of transient methods in geophysics.

Wait’s work concerning EM applications in mining production is perhaps less well known. A mine, surface or underground, is a hazardous work environment producing a commodity for national and international markets. Safety and production efficiency both must be achieved or the mine closes. In such an environment, several factors relating to electromagnetics are important. These include the following.

- 1) *Efficient communication between miners at all times.* Efficiency and safety require optimal communications between all production workers. When things go wrong, mine rescue is facilitated by communications being maintained by conventional or unconventional means.
- 2) *Evaluating and containing stray electrical currents.* Stray electrical signals can degrade communications, interfere with geophysical probing, prematurely fire electrical blasting caps, ignite methane-based mine explosions, and electrocute miners. EM theory is important in reducing these risks, even if it is not used routinely.

Manuscript received September 10, 1999; revised February 11, 2000. This work was supported in part by the DOE under Grant DE-AC07-95ID13274.

A. C. Tripp is with the Department of Geology and Geophysics, University of Utah, Salt Lake City, UT 84112 USA (e-mail: actripp@mines.utah.edu).

R. McNearny is with the Department of Mining Engineering, Montana Technological University, Butte, MT 59701-8997 USA (e-mail: rmcnearny@mtech.edu).

C. Furse is with the Department of Computer and Electrical Engineering, Utah State University, Logan, UT 84322 USA.

Publisher Item Identifier S 0018-926X(00)09368-6.

- 3) *Detection and imaging anomalous geology ahead of mining.* One of the main reasons for unexpected increases in the cost of mining strata-bound materials, such as coal, is anomalous geology. Paleochannels, faults, dikes, or sills, cutting through production zones affects product quality and producibility.

In these concerns, it is important to be able to calculate EM field strengths for conductor geometries corresponding to those maintained in a mine. The works of Prof. Wait address these problems.

In the following, we provide a bibliography of some Wait publications relevant to mining production technology. We also briefly present specific historical and potential applications of these theoretical publications. Our hope is that such a work, apart from commemorating the life and contributions of Prof. Wait, will increase the awareness of mining and its technological needs among the electrical engineering community.

## II. MINE COMMUNICATION

Communications in the underground mine setting is relatively new compared with the long history of mining, both in the United States as well as elsewhere in the world. Communications equipment did not start appearing in western U.S. underground workings until the early 1900s ([59], [60]). Early telephone sets were comparable to the standard aboveground sets of the day, except that they were contained in cast-iron casings to protect them from the underground environment. In the 1950s, the Chesapeake and Potomac Telephone Company developed an explosion-proof telephone set. Its utility was limited, however, because of the heavy casing around it. Telephone sets also required a conduit, which again limited their usefulness, given the size of many underground coal mines.

Although loudspeakers, bells and whistling signaling systems have been used recently, communication systems currently used in most mines in the U.S. include overhead trolley wire or a fixed pager phone. The trolley wire system is used mainly to schedule haulage. Pager systems, usually voice activated, are often broken down into multiple-part units that are often controlled by the mine dispatcher. Newer paging systems have been improved by the incorporation of computerized control, whereby an operator can type a message into a computer that either routes the specific digital message to one individual or to all miners within a working section. Such a paging system was effective during the mine fire at the Willow Creek Coal Mine in southern Utah on November 25, 1998, where the underground miners were quickly notified of evacuation by the mine’s paging system [67].

Also included under the heading of mine communications are monitoring systems which include sensors for methane, carbon monoxide, temperature, relative humidity, airflow, and differential pressure. The output from these sensors is now controlled by computers and is often incorporated into a display that provides operational monitoring of the mine, including the monitoring of production, materials handling, electrical systems, rockbursts, water levels in sumps, and methane drainage equipment [68].

The curious will find more extensive information concerning the history and practice of mine communications contained in supplemental references [59]–[74].

Establishing good communications underground can be difficult, since the mine environment is only partially amenable to human intervention. For example, many mining operations require metallic mechanical parts such as cables, cutting blades, or machinery. These metallic components can be thin and extended such as cables or can be discrete and massive such as continuous mining equipment. Rock encountered in the mine can range in conductivity over more than 12 orders of magnitude [70] and the conductivity varies over microscopic to mine dimension scales. Design of effective communications equipment in such conditions requires effective modeling, demonstrated in abundance by Wait and his colleagues.

The chronological bibliography of Prof. Wait's relevant publications reveals three major geometries related to mine communications. These are EM propagation in layered earths, EM propagation in tunnels, and EM propagation on cables and drill steel.

Ideally, mine communications should be able to access every part of the mine and its environs. Such a capacity requires through-the-earth communications, recently contemplated by U.S. mining companies, following the lead of several innovative mines in Australia. Modeling the effect of rock layers on the EM fields is critical in this application. Prof. Wait's work on layered earths was comprehensive in addressing continuous wave (CW) and transient problems over a range of conductivity and dielectric values. References [2], [3], [5], [7]–[15], [20], [26], [29], [38], [43], [51], and [55] are concerned with the problem of EM propagation through an earth—possibly with layers.

If miners are unable to access conventional communications equipment in an emergency, through-the-earth communications becomes critical. References [9], [11], [15], and [20] specifically address emergency communications systems in which trapped or barricaded miners activate a radio transmitter whose fields are detected by rescuers equipped with receivers [71]. The basic concept is similar to the Pieps system for locating avalanche victims. Such systems are not in general use today.

References [29], [43], [51], [55], and [72]–[74] are concerned with EM propagation in coal seams. These works are of interest to anyone interested in coal mine communication or in coal seam monitoring for long-wall operations. They are also important in coal seam tomography.

The reason for applying magnetic dipole antennas instead of electric dipole antennas in a slightly conducting media is explained in [58].

Mine radio communications can use tunnels as lossy waveguides. Wait and colleagues discuss tunnel waveguides in ref-

erences [4], [17], [21], [27], [33], [42], [50], and [57]. These works, with the exception of [21], use modal expansions with various boundary conditions. Reference [21] uses geometric optics to deal with rectangular tunnels.

A very popular method of mine communication is to use a cable within a tunnel, shaft, or drill hole. References [16], [18], [19], [22], [23], [25], [28], [30]–[32], [34]–[36], [38]–[41], [44]–[47], [49], [52], and [54] all present analyses of various engineering designs of cable-based communication. These references, which are still relevant to mining engineering, have in addition application to well logging in the oil industry and covert-tunnel detection. They also represent a remarkable illustration of the use of analytic methods.

A variation on cable-based communications is communications along a drill rod. This has application to the trapped miner problem and is considered in [48]. This work also has application to drill string telemetry for directional drilling.

### III. AMBIENT MINE ELECTRICAL FIELD ESTIMATION

An underground mine offers a peculiar electrical environment in which highly conductive material such as track or cables are superimposed on resistive access tunnels or shafts. The rock itself may be conductive or resistive—and the transition between the two may be abrupt. Highly conductive water may move through the mine, using small permeability conduits. Mining machinery in this environment may generate a great deal of EM noise. Atmospheric electricity can gain access to workings through external cables or rails.

Deducing the electromagnetic environment in a mine has several potential uses. Among them are:

- 1) the atmosphere in access areas may have an explosive mixture of methane, which may be detonated through stray sparks;
- 2) stray currents can interfere with ground conductor monitoring circuits, leading to electrocution hazards;
- 3) electric blasting caps can be detonated with a sufficiently large ambient electric field;
- 4) communications can be degraded or disrupted by conductive features or noise sources.

The work on wave propagation in tunnels and along conductors in tunnels is directly applicable to noise field estimation, impacting the safety concerns of electrocution from power distribution faults or accidental methane and electric blasting cap detonation. For example, Wait's publications could be used to estimate the electric field in a quartzite adit due to atmospheric electrical fields carried along tram lines onto ore car rails. As it happens, these fields can be sufficiently large to detonate electric blasting caps.

### IV. HISTORICAL RETROSPECTIVE AND FUTURE PERSPECTIVES

Perusal of the chronological list of references reveals clustering about the 1970s, a period in which technological innovations in mining were encouraged by private and public research funding. The work of Wait and colleagues, driven by the economic climate of the time, provided an archetypal use of analytic methods for modeling a complicated mining environment.

We believe that the importance of Wait's work endures and offers much of value to electrical engineers and mining engineers. Our reasons are the following.

- 1) The engineering problems addressed by Wait endure. Indeed, remote sensing, communications, and mine safety issues will probably become more important.
- 2) Many of the analytic models developed by Wait have contemporary application in areas other than mining. For example, Wait's analyses of antennas in lossy media have direct application in designing high-frequency antennas for high-resolution imaging of lossy geological material such as waste dumps. Likewise, his work in EM focusing [56], has application in such potential applications as joule heating for enhanced oil recovery. Propagation along a drill steel is also a viable model for drill-stem telemetry for measurement while drilling (MWD) in well-logging. Wait also examined the possibility of earth material waveguides and resonant loop detection of coal-boundary rock interfaces [43], which both have significance for cutting machine control. Resonant loop detection has also been suggested for plastic antipersonnel landmine detection.
- 3) While numerical methods continue to improve with improvements in software and hardware, each numeric algorithm is best used on specific types of problems. Analytic solutions such as those of Wait and colleagues, provide verification of these algorithms. It is also true that in certain problems, analytic methods provide the best solution.
- 4) Given the breadth and depth of Wait's work, it seems reasonable that future investigators will find many of their problems at least partially solved by a Wait paper.

In conclusion, we have found Wait's work to be of perennial interest. It is our hope that future workers, in the spirit of James Wait, will extend the scope and power of EM technology in mining production.

#### ACKNOWLEDGMENT

The authors would like to thank Prof. Wait for his generous professional interactions of over almost two decades. His influence will continue.

#### REFERENCES

- [1] J. R. Wait, "Transient electromagnetic propagation in a conducting medium," *Geophys.*, vol. 16, no. 4, pp. 213–221, 1951.
- [2] J. R. Wait and L. L. Campbell, "The fields of an oscillating magnetic dipole immersed in a semi-infinite conducting medium," *J. Geophys. Res.*, vol. 58, no. 2, pp. 167–178, 1953.
- [3] J. R. Wait, "Radiation from a small loop immersed in a semi-infinite conducting medium," *Canadian J. Phys.*, vol. 37, pp. 672–674, 1959.
- [4] —, *Electromagnetic Radiation from Cylindrical Structures*. New York: Pergamon, 1999.
- [5] —, "Electromagnetic waves in the earth," *IEEE Trans. Antennas Propagat.*, vol. AP-11, pp. 206–372, 1963.
- [6] —, "A fundamental difficulty in the analysis of cylindrical waveguides with impedance walls," *Electron. Lett.*, vol. 3, no. 2, pp. 87–88, 1967.
- [7] —, *Electromagnetic Waves in Stratified Media*. New York: Pergamon, 1999.
- [8] —, "Electromagnetic fields of a small loop buried in a stratified earth," *IEEE Trans. Antennas Propagat.*, vol. AP-19, pp. 717–718, 1971.
- [9] —, "Electromagnetic induction technique for locating a buried source," *IEEE Trans. Geosci. Electron.*, vol. GE-9, pp. 95–98, 1971.

- [10] —, "Transient fields from a buried magnetic dipole," *J. Appl. Phys.*, vol. 42, no. 10, pp. 3866–3869, 1971.
- [11] —, "Locating an oscillating magnetic dipole in the earth," *Electron. Lett.*, vol. 8, no. 16, p. 404, 1972.
- [12] —, "Theory of wave propagation along a thin wire parallel to an interface," *Radio Sci.*, vol. 7, no. 6, pp. 675–679, 1972.
- [13] NOAA Environ. Res. Lab., COM 72-11 510, 1972.
- [14] —, "Electromagnetic surface fields produced by a pulse-excited loop buried in the earth," *J. Appl. Phys.*, vol. 43, no. 10, pp. 3988–3991, 1972.
- [15] J. R. Wait, "State of knowledge of analytical techniques in through-the-earth electromagnetic wave problems relevant to mine rescue," *BuMines OFR 16-74*, pp. 9–14, 1973.
- [16] S. F. Mahmoud and J. R. Wait, "Theory of wave propagation along a thin wire inside a rectangular waveguide," *Radio Sci.*, vol. 9, pp. 417–420, Mar. 1974.
- [17] —, "Guided electromagnetic waves in a curved rectangular mine tunnel," *Radio Sci.*, vol. 9, pp. 567–572, May 1974.
- [18] J. R. Wait and D. A. Hill, "Guided electromagnetic waves along an axial conductor in a circular tunnel," *IEEE Trans. Antennas Propagat.*, vol. AP-22, pp. 627–630, July 1974.
- [19] D. A. Hill and J. R. Wait, "Gap excitation of an axial conductor in a circular tunnel," *J. Appl. Phys.*, vol. 45, pp. 4774–4777, Nov. 1974.
- [20] —, "Analytical investigations of electromagnetic location schemes relevant to mine rescue," *BuMines OFR 25-75*, p. 147, 1974.
- [21] S. F. Mahmoud and J. R. Wait, "Geometrical optical approach for electromagnetic wave propagation in rectangular mine tunnels," *Radio Sci.*, vol. 9, pp. 1147–1158, Dec. 1974.
- [22] J. R. Wait and D. A. Hill, "Coaxial and bifilar modes on a transmission line in a circular tunnel," *Appl. Phys.*, vol. 4, no. 4, pp. 307–312, 1974.
- [23] D. A. Hill and J. R. Wait, "Excitation of monofilar and bifilar modes on a transmission line in a circular tunnel," *J. Appl. Phys.*, vol. 45, no. 8, pp. 3402–3406, 1974.
- [24] D. C. Chang and J. R. Wait, "Extremely low frequency (ELF) propagation along a horizontal wire located above or buried in the earth," *IEEE Trans. Commun.*, vol. COM-22, pp. 421–426, 1974.
- [25] J. R. Wait and D. A. Hill, "Theory of the transmission of electromagnetic waves down a mine hoist," *Radio Sci.*, vol. 10, pp. 625–632, June 1975.
- [26] J. R. Wait, "Transient magnetic fields produced by a step-function-excited loop buried in the earth," *Electron. Lett.*, vol. 8, no. 11, pp. 294–295, 1975.
- [27] —, "Theory of EM wave propagation through tunnels," vol. 10, pp. 753–759, July 1975.
- [28] J. R. Wait and D. A. Hill, "Propagation along a braided coaxial cable in a circular tunnel," *IEEE Trans. Microwave Theory Tech.*, vol. MTT-23, pp. 401–405, 1975.
- [29] J. R. Wait, "Note on the theory of transmission of electromagnetic waves in a coal seam," *Radio Sci.*, vol. 11, pp. 263–265, Apr. 1976.
- [30] D. A. Hill and J. R. Wait, "Calculated transmission loss for a leaky feeder communication system in a circular tunnel," *Radio Sci.*, vol. 11, pp. 315–321, Apr. 1976.
- [31] J. R. Wait, "The eccentrically located wire in a cylindrical cavity in a conducting medium and the limit of a planar boundary," *Radio Sci.*, vol. 11, pp. 897–899, Nov. 1976.
- [32] D. A. Hill and J. R. Wait, "Analysis of radio frequency transmission along a trolley wire in a mine tunnel," *IEEE Trans. Electromagn. Compat.*, vol. EMC-18, pp. 1–16, Nov. 1976.
- [33] —, "Impedance of an electric dipole located in a cylindrical cavity in a dissipative medium," *Appl. Phys.*, vol. 11, pp. 351–356, Dec. 1976.
- [34] J. R. Wait and D. A. Hill, "Attenuation on a surface wave line suspended within a circular tunnel," *J. Appl. Phys.*, vol. 47, pp. 5472–5473, 1976.
- [35] J. R. Wait, "EM theory of the loosely braided coaxial cable," *IEEE Trans. Microwave Theory Tech.*, vol. MTT-24, pp. 262–265, 1976.
- [36] S. F. Mahmoud and J. R. Wait, "Calculated channel characteristics of a braided coaxial cable in a mine tunnel," vol. COM-24, pp. 82–87, 1976.
- [37] J. A. Fuller and J. R. Wait, "A pulsed dipole in the earth," in *Transient Electromagnetic Fields*, L. B. Felsen, Ed. New York: Springer-Verlag.
- [38] J. R. Wait and D. A. Hill, "Influence of spatial dispersion of the shield transfer impedance of a braided coaxial cable," *IEEE Trans. Microwave Theory Tech.*, vol. MTT-25, pp. 72–74, Jan. 1977.
- [39] —, "Radio frequency transmission via a trolley wire in a mine tunnel with a rail return," *IEEE Trans. Antennas Propagat.*, vol. AP-25, pp. 1–12, Mar. 1977.
- [40] —, "Electromagnetic fields of a dipole source in a circular tunnel containing a surface wave line," *Int. J. Electron.*, vol. 42, pp. 377–391, 1977.
- [41] J. R. Wait, "Quasi-static limit for the propagating mode along a thin wire in a circular tunnel," *IEEE Trans. Antennas Propagat.*, vol. AP-25, pp. 441–443, 1977.

- [42] J. R. Wait and D. A. Hill, "Subsurface EM transmission in tunnel waveguides," *Radio Sci.*, vol. 13, p. 402, Mar.–Apr. 1978.
- [43] D. C. Chang and J. R. Wait, "An analysis of a resonant loop as an electromagnetic sensor of coal seam thickness," *Radio Sci.*, vol. 13, p. 399, Mar.–Apr. 1978.
- [44] D. A. Hill and J. R. Wait, "The impedance of dipoles in a circular tunnel with an axial conductor," *IEEE Trans. Geosci. Electron.*, vol. GE-16, pp. 118–126, Apr. 1978.
- [45] J. R. Wait and D. A. Hill, "Analysis of the dedicated communication line in a mine tunnel for a shunt-loaded trolley wire," *IEEE Trans. Commun.*, vol. COM-26, pp. 355–361, 1978.
- [46] D. A. Hill and J. R. Wait, "Bandwidth of a leaky coaxial cable in a circular tunnel," *IEEE Trans. Commun.*, vol. COM-62, pp. 1765–1771, 1978.
- [47] D. B. Seidel and J. R. Wait, "Transmission models in a braided coaxial cable and coupling to a tunnel environment," *IEEE Trans. Microwave Theory Tech.*, vol. MTT-26, pp. 494–499, 1978.
- [48] D. A. Hill and J. R. Wait, "Calculated admittance of an idealized drill rod antenna in a lossy medium," *IEEE Trans. Antennas Propagat.*, vol. AP-27, Sept. 1979.
- [49] ———, "Propagation along a coaxial cable with a helical shield," *IEEE Trans. Microwave Theory Tech.*, vol. MTT-28, pp. 84–89, 1980.
- [50] J. R. Wait, "Propagation in rectangular tunnel with imperfectly conducting walls," *Electron. Lett.*, vol. 16, pp. 521–522, June 1980.
- [51] M. A. Ralston and J. R. Wait, "Theory of low-frequency conductivity probing of roof structures in coal mines," *Radio Sci.*, vol. 15, pp. 1105–1108, Nov.–Dec. 1980.
- [52] D. A. Hill and J. R. Wait, "EM theory of the loosely braided coaxial cable—Numerical results," *IEEE Trans. Microwave Theory Tech.*, vol. MTT-28, pp. 326–331, 1981.
- [53] ———, "Theoretical noise and propagation models for through-the-earth communications," U.S. Bureau Mines Rep., Contract J0 113 0581, May 1982.
- [54] J. R. Wait, "Electromagnetic wave transmission in a well logging cable-theory," *IEEE Trans. Microwave Theory Tech.*, vol. 38, pp. 1518–1521, Oct. 1990.
- [55] ———, "Radiowave propagation in a coal seam with inhomogeneous rock walls," *IEEE Trans. Geosci. Remote Sensing*, vol. 29, pp. 469–472, May 1991.
- [56] K. A. Nabulsi and J. R. Wait, "Space and time wave shaping for transmission into a lossy medium," *IEEE Trans. Antennas Propagat.*, vol. 41, pp. 727–731, June 1993.
- [57] J. R. Wait, "Electromagnetic guided cylindrical waves in tunnels," in *Proc. Int. Symp. Electromagn. Compat.*, 1996.
- [58] ———, "The possibility of guided electromagnetic waves in the earth's crust," *IEEE Trans. Antennas Propagat.*, vol. AP-1, May 1952.
- [59] J. R. Anon, "Underground mine communications," U.S. Bureau Mines Circulars, IC 8742, 1977. (in four parts).
- [60] ———, "Underground mine communications," U.S. Bureau Mines, IC 8955, 1984. (in four parts).
- [61] P. Delogne, "Les communications par radio en milieu souterrain," *Acta Tech.*, vol. 9, no. 2, pp. 18–26, 1973.
- [62] P. Delogne, L. Deryck, and R. Liegeois, "Guided propagation of radio waves," in *Proc. Thru Earth Electromagn. Workshop*. Golden, CO, Aug. 1973, pp. 49–53.
- [63] L. Deryck, "Etude de modes de propagation d'ondes electromagnetique, susceptibles d'exister sur une ligne bifilaire en milieu souterrain," *Ann. Mines*, vol. 7, no. 8, pp. 939–949, 1970.
- [64] ———, "Radiocommunication in tunnels," *Electron. Lett.*, vol. 8, no. 3, pp. 71–72.
- [65] ———, "Etude de la propagation des ondes electromagnetique guidees dans les galerie souterraines," These de doctorat, Univ. Liege, Liege, Belgium.
- [66] J. Fontaine, B. Demoulin, P. Degauque, and R. Gabillard, "Feasibility of radio communication in mine galleries by means of a coaxial cable having a high coupling impedance," in *Proc. Thru Earth Electromagn. Workshop*. Golden, CO, Aug. 1973, pp. 130–139.
- [67] D. Hinkins, "Underground paging systems—Application and performance," in *Technical Session I: New Directions 30th Annu. Inst. Mining Health, Safety, Res.*, Salt Lake City, UT, Aug. 1999.
- [68] J. Kohler, *Monitoring, Control, and Communications*. Littleton, CO: Soc. Mining, Metallurgy, Exploration, 1992, SME Mining Engrg. Handbook, ch. 12.6.
- [69] D. J. R. Martin, "Radiocommunication in mines and tunnels," *Electron. Lett.*, vol. 6, no. 18, pp. 563–564, 1970.
- [70] E. I. Parkomenko, *Electrical Properties of Rocks*. New York: Plenum, 1967.
- [71] J. A. Powell, "An electromagnetic system for detecting and locating trapped miners," U.S. Bureau Mines, IC 8955. (in four parts).
- [72] R. E. Collins and F. J. Zucker, *Antenna Theory—Part 2*. New York: McGraw-Hill, 1999.
- [73] D. A. Hill, "Propagation in a coal seam and the inverse problem," *J. Res.*, vol. 89, no. 5, Sept.–Oct. 1984.
- [74] L. G. Stolarczyk and R. C. Fry, "Radio imaging method (RIM) for diagnostic imaging of anomalous geological structures in coal seam wave guides," *Trans. Soc. Mining Metallurgy, Exploration*, vol. 288, pp. 1806–1814.

**A. C. Tripp** received the B.A. degree in mathematics from Michigan State University, East Lansing, in 1973, and the the M.S. and Ph.D. degrees in geophysics from the University of Utah, Salt Lake City, both in 1982.

He is currently a Research Associate Professor of geophysics with the University of Utah, Salt Lake City. He was an Adjunct Associate Professor of mining engineering at Montana Tech, University of Montana, Butte, and an Adjunct Research Professor of electrical engineering at Utah State University, Logan. His research interests are in the collection, presentation, and processing of electrical and electromagnetic data for geological and geotechnical imaging, electromagnetic data enhancement and fusion, and cognitive aspects of geophysical interpretation.

**R. McNearney** received the B.S. and M.S. degrees in civil engineering from the University of Colorado, Denver, in 1977 and 1982, respectively, and the Ph.D. degree in mining engineering from the Colorado School of Mines, Golden, in 1991.

He is currently the Anaconda Endowed Professor of mining engineering at Montana Tech, University of Montana, Butte. He has worked as an Assistant and Associate Professor at the University of Utah, Salt Lake City, from 1991 to 1999 and also as an engineer with the U.S. Bureau of Reclamation from 1978 to 1990. His research interests are in the investigation, analysis, and numerical modeling of mining, civil construction and geomechanical systems, all aspects of environmental remediation, and environmental permitting of industrial facilities.

**C. Furse**, biography and photograph unavailable at time of publication.